


**Model No: AIH501**

## Features

Input: 24V DC Power Supply, Grey Color, with Flasher & Acknowledgement Push button, IP-66 Rating, "Ex-d" Gas group: IIB, Type of Ex-Protection: AS PER IS/ IEC- 60079-1:2007, CIMFR approved, Gland Cable Entry: 02 Nos. for M20 (3/4" ET)

## Specifications

Type of Ex-Protection	AS PER IS / IEC-60079-1:2007
Zone Classification	Zone 1 & Zone 2
Ingress IP Protection	IP-65 IS IEC60529-2001
Auxiliary Supply	230V AC OR 24V DC As Per Requirements
Power Consumption	450 mA@ 24VDC& 80mA@230VAC
Audio Range	80 db (Pulsating)
Flasher	Led Type (Optional As Per Client Requirements)
Terminal	2.5 sq. mm Elmax Terminal
Material of contraction	Die Cast Aluminum Alloy LM6
Paint	Epoxy Polyester Powder Coating
Earthling	Internal: 01 No. & External: 2 Nos.
Cable Entry	02 Nos. for M20 (3/4" ET)
Hardware	Stainless Steel

Hyderabad Office: H. no : 08-041/1, Plot no 132, N C L Enclave, Kompally,  
Hyderabad, Telangana, India - 500067.

✉ [admin@arkainstruments.com](mailto:admin@arkainstruments.com) | ☎ [www.arkainstruments.com](http://www.arkainstruments.com)

📞 +91 81438 12346